



ISO cylinder, DSBC-32-25-PPVA-N3

1376422

URL:<https://www.sxplc.com/iso-cylinder-dsbc-32-25-ppva-n3-1376422>

Product data sheet

- | |
|---|
| • Stroke 25 mm |
| • Piston diameter 32 mm |
| • Piston rod thread M10x1.25 |
| • Cushioning Pneumatic cushioning, adjustable at both ends |
| • Mounting position Any |
| • Conforms to standard ISO 15552 |
| • Piston rod end External thread |
| • Structural design Piston Piston rod Profile barrel |
| • Position sensing For proximity sensor |
| • Symbol 00991235 |
| • Variants Piston rod at one end |
| • Operating pressure 0.06 MPa ... 1.2 MPa |
| • Operating pressure 0.6 bar ... 12 bar |
| • Mode of operation Double-acting |

- **Operating medium** Compressed air as per ISO 8573-1:2010 [7:4:4]
- **Information on operating and pilot media** Operation with oil lubrication possible (required for further use)
- **Corrosion resistance class (CRC)** 2 - Moderate corrosion stress
- **LABS (PWIS) conformity** VDMA24364-B1/B2-L
- **Cleanroom class** Class 6 according to ISO 14644-1
- **Ambient temperature** -20 °C ... 80 °C
- **Impact energy in the end positions** 0.4 J
- **Cushioning length** 17 mm
- **Theoretical force at 6 bar, retracting** 415 N
- **Theoretical force at 6 bar, advancing** 483 N
- **Moving mass at 0 mm stroke** 110 g
- **Additional moving mass per 10 mm stroke** 9 g
- **Basic weight with 0 mm stroke** 465 g
- **Additional weight per 10 mm stroke** 27 g
- **Type of mounting** Optionally: With internal thread With accessories
- **Pneumatic connection** G1/8
- **Note on materials** RoHS-compliant
- **Cover material** Die-cast aluminum, coated
- **Piston seal material** TPE-U(PU)
- **Material of piston** Wrought aluminum alloy
- **Piston rod material** High-alloy steel
- **Piston rod wiper material** TPE-U(PU)

- **Buffer seal material**TPE-U(PU)
- **Cushion piston material**POM
- **Material of cylinder barrel**Wrought aluminum alloy, smooth-anodized
- **Nut material**Steel, galvanized
- **Material of bearing**POM
- **Flange screws material**Steel, galvanized

