



## **Automatic Float Drain: M12.FD.0001**

URL:<https://www.sxplc.com/automatic-float-drain-m12-fd-0001>

### **Product data sheet**

#### Dimensions

Width (In.) 0.95 in

Base Dia. (In.) 0.95 in

Height (In.) 3.23 in

#### Details

Function Clamps and Tie Rod Kits Connect Multiple Filter Housings, Incident Motor Used to Indicate Premature High Differential Pressure, Mounting Brackets Provide Support to Filters Installed in Flexible Piping Systems or OEM Equipments

For Use With Model Number 010-055

Item Automatic Float Drain

Connection Female

Application Compressed Air Filters

Provides Mounting Brackets Provide Support to Filters Installed in Flexible Piping Systems or OEM Equipment

Replaces PD15NO

For Use On OIL-X Compressed Air Filter, OIL-X EVOLUTION Compressed Air Filter

Fitting 1/4 in to 4 in Models

Adjustment Range (PSI) 22 to 232 psi

Max. Working Pressure (PSI) 232 psi

Max. Pressure (PSI) 232 psi

Includes Clamps, Incident Monitors, Mounting Bracket Kits, O Ring Kits, Replacement Drains, Tie Rod Kits

Type Automatic Float Drain

Design Type Automatic Float Drain

For Use on Filter Parker OIL-X Models 010-055

Fits OIL-X Compressed Air Filter, OIL-X EVOLUTION Compressed Air Filter

