

# Plug valve lubricant and sealant

## P13336

URL:<https://www.sxplc.com/plug-valve-lubricant-and-sealant-p13336>

### Product data sheet

Technical data □QTY□1 box includes 10 pcs?price for 1 pcs□

---

Dropping point: no dropping point

Base oil: synthetic oil polymerised hydrocarbon derivatives

Shelf life: 5 years (under controlled environment)

Oxidative stability: Very good

Temperature Range: 32°F to 400°F

PERMEABILITY

(Bulk): NLGI Grade #3 (ASTM 220-250)

(Tube): NLGI Class #6 (NSTM 85-115)

Thickener: Inorganic

Fillers: Rheological additives

Colour: Brown

Weight: 0.35kg/pc

Carton size: 30cm \* 23.5cm \* 10cm

Product description

---

Non-Toxic Hazardous Materials

Lightning 400 degrees Fahrenheit and above

Non-flammable

Country of origin: USA

The sealant is particularly suitable for direct or conical plug valves has excellent viscosity and adhesion. This product has excellent resistance to aliphatic hydrocarbon liquids and gases, crude oil distillates fractional oils, fuels and lubricants, sweet or sour gas, paraffin, gasoline, aqueous solutions and water.

#### Instructions for use

---

Not for use in alkali or amine service

---

