



Cylinder DSNU-12-15-P-A 1908255

URL:<https://www.sxplc.com/cylinder-dsnu-12-15-p-a-1908255>

Product data sheet

stroke

15 mm

Piston diameter

12 mm

Thread of piston rod

M6

buffer

Elastic buffer rings/pads at both ends

Installation location

Optional

Compliant with standards

CETOP RP 52 P

ISO 6432

End of piston rod

External thread

Structural characteristics

Cylinder diameter

piston rod

Cylinder barrel

position detection

By proximity switch

symbol

00991217

Derived type

One end piston rod

working pressure

0.15 Mpa 1 Mpa

working pressure

1.5 bar 10 bar

Working mode

Double action

Working medium

Compressed air, in accordance with ISO 8573-1:2010 [7:4:4]

Description of Work and Pilot Media

Can work with lubricating medium (must continue to work with lubricating medium thereafter)

Corrosion resistance grade CRC

2- Moderate corrosion resistance

Paint Wetting Defect Substance (PWIS) Compliance

VDMA24364-B1/B2-L

Cleanroom level

Level 6, in accordance with ISO 14644-1

ambient temperature

-20 ° C 80 ° C

Impact energy at the end position

0.07 J

Theoretical force value at 6 bar, return stroke

50.9 N

Theoretical force value at 6 bar, forward travel

67.9 N

Moving mass with a 0 mm stroke

18.5 g

Extra moving mass per 10 mm stroke

2 g

Basic weight of 0 mm stroke

75 g

Additional weight for every 10 meters of travel

4 g

Installation method

With attachments

Pneumatic interface

M5

Material Description

RoHS compliance

Lid material

Refined aluminum alloy

Colorless anodizing

Sealing material

NBR

TPE-U (PU)

Material of piston rod

High alloy stainless steel

Cylinder material

High alloy stainless steel

