



## **Connector, 1309426003-E**

URL:<https://www.sxplc.com/connector-1309426003-e>

**Product data sheet**

## Technical Data

### General Data

|   |  |
|---|--|
| Fields of application                         | office areas                           |
| Mechanical measurement according to MICE      | M1                                     |
| Ingress measurement according to MICE         | I1                                     |
| Climatic measurement according to MICE        | C1                                     |
| Electromagnetic measurement according to MICE | E2                                     |
| Design  | wall outlet                            |
| Mounting style                                | Standard rail TH35                     |
| Shielding                                     | shielded                               |
| Transmission technology                       | Copper                                 |
| Wiring  | T568A and T568B                        |
| Color   | light gray                             |
| Dimensions                                    |  |
| Dimension (L x W x H)                         | 60 mm x 17.5 mm x 52.2 mm              |
| Dimension (L x W x H)                         | 2.362 in. x 0.689 in. x 2.055 in.      |
| Horizontal pitch                              | 1HP                                    |
| Labeling option                               | label window with identification label |
| Marking option                                | by dust protection                     |

### Transmission characteristics

|                                 |                |
|---------------------------------|----------------|
| Category (ISO)                  | 6 <sub>A</sub> |
| Class (ISO/IEC)                 | E <sub>A</sub> |
| Category (TIA)                  | 6A             |
| Remote Powering                 | yes            |
| PoE                             | IEEE 802.3af   |
| PoE plus                        | IEEE 802.3at   |
| UPoE                            | yes            |
| 4PPoE                           | IEEE 802.3bt   |
| HDBaseT                         | yes            |
| Transmission rate up to 10 GBit | IEEE 802.3an   |

