



Screw joint QSLV-1/4-8-50 130753

URL:<https://www.sxplc.com/screw-joint-qslv-1-4-8-50-130753>

Product data sheet

specifications

standard

Nominal diameter

5 mm

The type of seal that is screwed into the screw

coating

Installation location

Optional

design

L-shaped

Package specifications

fifty

Structural characteristics

Push-pull principle

Complete temperature range under working pressure

-0.095 Mpa 0.6 Mpa

Working pressure complete temperature range

-0.95 bar 6 bar

Complete temperature range under working pressure

-13.775 psi 87 psi

Working pressure dependent on temperature

-0.095 Mpa 1.4 Mpa

Working pressure dependent on temperature

-0.95 bar 14 bar

Working pressure dependent on temperature

-13.775 psi 203 psi

Working medium

Compressed air, in accordance with ISO 8573-1:2010 [7: -: -]

The moisture content complies with the manufacturer's declaration of conformity on www.festo.com

Description of Work and Pilot Media

Working with lubricating media available

Corrosion resistance grade CRC

1- Low corrosion resistance

Paint Wetting Defect Substance (PWIS) Compliance

VDMA24364-B1/B2-L

Cleanroom level

Level 4, in accordance with ISO 14644-1

ambient temperature

-10 ° C 80 ° C

Nominal torque

9 Nm

Nominal tightening torque tolerance

$\pm 20\%$

Product weight

38 g

Installation method

Hollow bolt, outer hexagon

Air interface, air port 1

External thread R1/4

Air interface, air port 2

Suitable for tracheal outer diameter of 8 mm

Release Ring Color

blue

Material Description

RoHS compliance

Shell material

PBT

Hollow bolt material

Nickel plated brass

Release ring material

POM

Material of tracheal seal

NBR

Material of tracheal clamping element

High alloy stainless steel

