



Soft starter PSTX210-600-70

URL:<https://www.sxplc.com/soft-starter-pstx210-600-70>

Product data sheet

Analog Outputs:

0...10 V, 0...20 mA, 4...20 mA

Signal Indication Ready to Start/Standby ON (LED):

Green

Signal Indication Running R (LED):

Green

Signal Indication Protection (LED):

Yellow



Signal Indication Fault (LED):

Red

Communication:

Modbus-RTU; Modbus-TCP; Ethernet-IP; EtherCAT; DeviceNet; CANopen;
Profibus; Profinet; BACnet-IP; BACnet-MSTP

Degree of Protection:

IP00



Terminal Type:

Main Circuit: Bars

Connecting Capacity Main Circuit:

Hole Diameter 10.2 mm

Connecting Capacity Control Circuit:

Rigid 1 x 2.5 mm²



Connecting Capacity Supply Circuit:

Rigid 1 x 2.5 mm²

Tightening Torque:

Main Circuit 25 N·m

Rated Operational Voltage:

208 ... 600 V AC

Rated Control Supply Voltage (U_s):

100 ... 250 V AC

Rated Control Circuit Voltage (U_c):

24 V DC

Rated Frequency (f):

50/60 Hz

Main Circuit 50 / 60 Hz

Rated Operational Power - In-Line Connection (Pe):

(230 V) 59 kW

(400 V) 110 kW

(500 V) 132 kW

Rated Operational Current - In-Line Connection (I_e):

210 A

Rated Operational Power - Inside Delta Connection:

at 230 V 102 kW

at 400 V 184 kW

at 500 V 250 kW

Rated Operational Current - Inside Delta Connection:

360 A



Product Net Width:

258 mm

Product Net Height:

470 mm

Product Net Depth / Length:

279 mm

Product Net Weight:

13.3 kg



