

# Shut off valve□HE-D-MAXI

URL:<https://www.sxplc.com/shut-off-valve-he-d-maxi>

## Product data sheet

• <b>Structural design</b>	Piston gate valve
• <b>Actuation type</b>	Manual
• <b>Sealing principle</b>	Soft
• <b>Exhaust air function</b>	Without flow control option
• <b>Manual override</b>	None
• <b>Symbol</b>	I00995571
• <b>Valve function</b>	3/2, bistable
• <b>Operating pressure</b>	0 MPa ... 1.6 MPa
• <b>Operating pressure</b>	0 bar ... 16 bar
• <b>Operating medium</b>	Compressed air as per ISO 8573-1:2010 [7:4:4] Inert gas
• <b>Information on operating and pilot media</b>	Operation with oil lubrication possible (required for further use)
• <b>Corrosion resistance class (CRC)</b>	2 - Moderate corrosion stress
• <b>Note on materials</b>	RoHS-compliant

- **LABS (PWIS) conformity**VDMA24364-B1/B2-L
- **Temperature of medium**-10 °C ... 60 °C
- **Ambient temperature**-10 °C ... 60 °C
- **Type of mounting**Line installation With accessories
- **Mounting position**Any
- **Flow direction**Non-reversible
- **Product weight**796 g
- **Pneumatic connection** 3G3/8
- **Air quality class at the output**Compressed air as per ISO 8573-1:2010 [7:4:4] Inert gas
- **Seals material**NBR
- **Housing material**Die-cast aluminum

