



With cable socket

KMEB-1-24-2.5-LED 151688

URL:<https://www.sxplc.com/with-cable-socket-kmeb-1-24-2-5-led-151688>

Product data sheet

Signal status display

Yellow LED

Installation location

Optional

Product weight

125 g

Electrical Interface 1

Socket, according to EN 175301-803 standard, type C

Electrical Interface 1, Design

right-angle

Electrical interface 1, connection type

Socket

Electrical interface 1, cable outlet

right-angle

Electrical Interface 1, Explanation on Cable Outlets

90°

Electrical interface 1, interface/number of wire cores

three

Electrical interface 1, installation type

Installed on the solenoid valve through M2.5 central screw

Electrical interface 2, connecting the system

Open

Electrical interface 2, interface/number of wire cores

three

Nominal working voltage DC

24 V

Surge resistance

0.8 kV

Protective wire interface

available

Cable length

2.5 m

Cable characteristics

standard

Cable diameter

5.2 mm

Cable structure

3 x 0.5 mm²

Line end

Core wire conduit

Protection level

IP65

Complies with IEC 60529 standard

ambient temperature

-20 °C ... 80 °C

CE certification (see declaration of conformity)

Compliant with EU RoHS Directive

CE marking (see declaration of conformity)

Compliant with UK RoHS Directive

Paint Wetting Defect Substance (PWIS) Compliance

VDMA24364-B2-L

class of pollution

three

Corrosion resistance grade CRC

1- Low corrosion resistance

Cable sheath material

PVC

Shell material

PA66-GF30

Sealing material

NBR

Electrical contact material

Silver plated copper alloy

