



## Proportional spool valve

### WDPFA06-ACB-S-5-G24/WD

URL: <https://www.sxplc.com/proportional-spool-valve-wdpfa06-acb-s-5-g24-wd>

## Product data sheet

Proportional spool valve WDPFA06-ACB-S-5-G24/WD

Flange construction

Q<sub>max</sub> = 42 l/min

4 volume flow levels

Q<sub>N</sub> max = 32 l/min

p<sub>max</sub> = 350 bar

# TYPE CODE

WD P F A06 -  -  -  /   -    #

Spool valve, direct operated																						
Proportional																						
Flange construction																						
International standard interface ISO, NG6																						
Designation of symbols acc. to table																						
Nominal volume flow rate $Q_N$	5 l/min	<input type="text" value="5"/>	16 l/min	<input type="text" value="16"/>	10 l/min	<input type="text" value="10"/>	32 l/min	<input type="text" value="32"/>														
Nominal voltage $U_N$	12 VDC	<input type="text" value="G12"/>	24 VDC	<input type="text" value="G24"/>	without coil		<input type="text" value="X5"/>															
Slip-on coil	Metal housing, round		<input type="text" value="W"/>		Metal housing, square		<input type="text" value="M"/>															
Connection execution	Connector socket EN 175301-803 / ISO 4400		<input type="text" value="D"/>		Connector socket AMP Junior-Timer		<input type="text" value="J"/>		Connector Deutsch DT04 - 2P		<input type="text" value="G"/>											
Sealing material	NBR		<input type="text"/>		FKM (Viton)		<input type="text" value="DT"/>															
Manual override	Integrated		<input type="text"/>		Push-button		<input type="text" value="HF1"/>		Spindle		<input type="text" value="HS1"/>											
Surface protection	Standard		<input type="text"/>		Zinc-nickel		<input type="text" value="K8"/>															
Design index (subject to change)																						

1.10-77

