



Plug ACP6034BC

URL: <https://www.sxplc.com/plug-acp6034bc>

Product data sheet

Features

- Interlocked rim connects with a ratchet, provides safe connect and disconnect.
- Safety cover lid, fully retractable, provides full protection and full inspection.
- Powerlite 3 Series plug fits hazardous locations 50 Amp, 60 Amp, 100 Amp, 150 Amp, 200 Amp, 250 Amp, 300 Amp, 400 Amp, 500 Amp, 600 Amp, 700 Amp, 800 Amp, 900 Amp, 1000 Amp, 1200 Amp, 1500 Amp, 2000 Amp, 2500 Amp, 3000 Amp, 4000 Amp, 5000 Amp, 6000 Amp, 7000 Amp, 8000 Amp, 9000 Amp, 10000 Amp.

Specifications

Hazardous Area Classification

Class I, Division 1 and 2, Groups B, C, D; Class II, Division 1 and 2, Groups F, G; Class III; NEMA 3, 3R, 4, 4X, 7CD, 9FG

Amperage

30, 60 or 100

Voltage

120 Vac, 240 Vac, 480 Vac or 600 Vac

Number of Poles

4

Number of Wires

3

Plug Cable Diameter

30 Amp: 0.500 to 1.125#8221;, 60 Amp: 0.500 to 1.375#8221;,
100 Amp: 0.875#8221; to 1.906#8221;

Wire Range

30 Amp: #10-#8, 60 Amp: #6-#4, 100 Amp: #2-1/0

Feed-Thru

Materials and Finishes

Receptacles, mounting box, covers and plug housings are copperfree (4/10 of 1% max.) aluminum with epoxy powder coat. Insulating blocks are fiber glass reinforced polyester.

