



Relay,3RN2012-2BW30

URL:<https://www.sxplc.com/relay-3rn2012-2bw30>

Product data sheet

product brand name	SIRIUS
product category	SIRIUS 3RN2 thermistor motor protection
product designation	Thermistor motor protection relay
design of the product	Standard evaluation unit with ATEX approval, open-circuit and short-circuit detection in the sensor circuit, non-volatile
product type designation	3RN2
General technical data	
product function	thermistor motor protection
display version LED	Yes
insulation voltage for overvoltage category III according to IEC 60664 with degree of pollution 3 rated value	300 V
degree of pollution	3
surge voltage resistance rated value	4 kV
protection class IP	IP20
shock resistance according to IEC 60068-2-27	11g / 15 ms
mechanical service life (operating cycles) typical	10 000 000
electrical endurance (operating cycles) at AC-15 at 230 V typical	100 000
thermal current of the switching element with contacts maximum	5 A
reference code according to IEC 81346-2	K
Substance Prohibittance (Date)	05/28/2009
SVHC substance name	Lead - 7439-92-1 Lead monoxide (lead oxide) - 1317-36-8 Dicyclohexyl phthalate (DCHP) - 84-61-7
Product Function	
product function	
<ul style="list-style-type: none"> • error memory • dynamic open-circuit detection • external reset • auto-RESET • manual RESET 	<ul style="list-style-type: none"> Yes Yes Yes Yes Yes
Control circuit/ Control	
type of voltage of the control supply voltage	AC/DC
control supply voltage at AC	
<ul style="list-style-type: none"> • at 50 Hz rated value • at 60 Hz rated value 	<ul style="list-style-type: none"> 24 ... 240 V 24 ... 240 V
control supply voltage at DC rated value	
<ul style="list-style-type: none"> • 	<ul style="list-style-type: none"> 24 ... 240 V

