



**BB230CS, Supply voltage [V] AC:  
230, Industrial pack 018F8363**

URL:<https://www.sxplc.com/bb230cs-supply-voltage-v-ac-230-industrial-pack-018f8363>

**Product data sheet**

Product details

Gross weight	0.265 Kilogram
Net weight	0.262 Kilogram
Volume	0.162 Liter
EAN	5702428170765
Actuator size	13.5 mm

Ambient temperature range [°C] [max]	50 °C
Ambient temperature range [°C] [min]	-40 °C
Ambient temperature range [°F] [max]	122 °F
Ambient temperature range [°F] [min]	-40 °F
Approval	CE EAC LLC CDC TYSK UKCA
China RoHS compliance	Out of scope
Coil connection	DIN Spade
Coil design standard	VDE 0580
Coil fastening	Clip-on
Coil winding insulation class	Class H to IEC 85
Colour	Blue
Compliance	EN 60730-1
Duty rating	Continuous
EEE category	5 small equipment (any external dimension 50 cm)?
Electrical connection	DIN Spade
Electrical connection size	6.3 mm x 0.8 mm
Electrical connection standard	EN175301-803
Electrical connector	3 x spades
Enclosure rating IP	IP00
EU RoHS compliance	Out of scope
Frequency [Hz]	50/60 Hz
Identical product	018F7363
In scope of WEEE	Yes
In scope of WEEE and contain batteries	No
Packing format	Industrial pack

	EV310B
Power consumption 50Hz [VA]	E12V0B
Power consumption 60Hz [VA]	E12V2B
Power consumption [W] 50Hz	EV220B W5 - 50
Power consumption [W] 60Hz	EV220B W6 - 22
Product accessories	Solenoid accessories
Product group	Solenoid valves
Product Name Description	Solenoid coil
Quantity per packing format	E5050B
REACH Candidate List substances	Lead (CAS 139-92-1)
Rel. Humidity [% RH] [max]	97 %
Rel. Humidity [% RH] [min]	0 %
Rel. Humidity conditions	Non-condensation
SCIP dossier no.	23785618-b379-4da7-a913-ecd40c8fae6d
SCIP dossier product name	Solenoid coils
Serviceable	No
Spare part number	018F7363
Supply voltage 50Hz Max [V]	230 V
Supply voltage 60Hz Max [V]	230 V
Supply voltage [V] AC	230 V
Type	BB230CS
Type designation	BB230CS
UK RoHS compliance	Out of scope

