



## **Cylinder ADVU-25-5-A-P-A 156608**

URL:<https://www.sxplc.com/cylinder-advu-25-5-a-p-a-156608>

### **Product data sheet**

trip

5 mm

Piston diameter

25 mm

buffer

Elastic buffer rings/pads at both ends

Installation location

Optional

Working mode

Double action

End of piston rod

External thread

Structural characteristics

Cylinder diameter

piston rod

position detection

By proximity switch

Symbol

00991217

Derived type

One end piston rod

working pressure

0.1 Mpa ... 1 Mpa

working pressure

1 bar ... 10 bar

working pressure

14.5 psi ... 145 psi

Working medium

Compressed air, in accordance with ISO 8573-1:2010 [7:4:4]

Description of Work and Pilot Media

Can work with lubricating medium (must continue to work with lubricating medium thereafter)

Corrosion resistance grade CRC

2- Moderate corrosion resistance

Paint Wetting Defect Substance (PWIS) Compliance

VDMA24364-B1/B2-L

ambient temperature

-20 °C ... 80 °C

Impact energy at the end position

0.1 J

Theoretical force value at 6 bar, return stroke

247 N

Theoretical force value at 6 bar, forward travel

295 N

Moving mass with a 0 mm stroke

26 g

Extra moving mass per 10 mm stroke

6 g

Basic weight of 0 mm stroke

180 g

Additional weight for every 10 meters of travel

28 g

Installation method

or

With through-hole

With attachments

Pneumatic interface

M5

Ring screw material

Galvanized steel

Lid material

Refined aluminum alloy

Dynamic sealing material

NBR

TPE-U(PU)

Material of piston rod

High alloy stainless steel

Cylinder material

Refined aluminum alloy

