



Distributor block □ MS6-FRM-FRZ

URL: <https://www.sxplc.com/distributor-block-ms6-frm-frz>

Product data sheet

- | |
|---|
| • Mounting position Any |
| • Structural design Branching module |
| • Symbol 00991510 |
| • Operating pressure 0 bar ... 20 bar |
| • Standard nominal flow rate in main flow direction 1 -> 214600
l/min |
| • Standard nominal flow rate outlet at top 10400 l/min |
| • Standard nominal flow rate outlet down 9850 l/min |
| • Certification cn UL us - Recognized (OL) |
| • Operating medium Compressed air as per ISO 8573-1:2010 [7:4:4]
Inert gas |
| • Information on operating and pilot media Operation with oil
lubrication possible (required for further use) |
| • Corrosion resistance class (CRC) 2 - Moderate corrosion stress |
| • LABS (PWIS) conformity VDMA24364-B1/B2-L |

- **Storage temperature**-10 °C ... 60 °C
- **Temperature of medium**-10 °C ... 60 °C
- **Ambient temperature**-10 °C ... 60 °C
- **Product weight**163 g
- **Pneumatic connection 3G1/2**
- **Pneumatic connection 4G1/2**
- **Note on materials**RoHS-compliant
- **Housing material**Die-cast aluminum

