



## Distributor block □ MS6-FRM-FRZ

URL: <https://www.sxplc.com/distributor-block-ms6-frm-frz>

### Product data sheet

- |   |
|---|
| • <b>Mounting position</b> Any  |
| • <b>Structural design</b> Branching module   |
| • <b>Symbol</b> 00991510  |
| • <b>Operating pressure</b> 0 bar ... 20 bar  |
| • <b>Standard nominal flow rate in main flow direction 1 -&gt;</b> 214600<br>l/min                                      |
| • <b>Standard nominal flow rate outlet at top</b> 10400 l/min   |
| • <b>Standard nominal flow rate outlet down</b> 9850 l/min  |
| • <b>Certification</b> nc UL us - Recognized (OL)   |
| • <b>Operating medium</b> Compressed air as per ISO 8573-1:2010 [7:4:4]<br>Inert gas                                    |
| • <b>Information on operating and pilot media</b> Operation with oil<br>lubrication possible (required for further use) |
| • <b>Corrosion resistance class (CRC)</b> 2 - Moderate corrosion stress   |
| • <b>LABS (PWIS) conformity</b> VDMA24364-B1/B2-L   |

- **Storage temperature**-10 °C ... 60 °C
- **Temperature of medium**-10 °C ... 60 °C
- **Ambient temperature**-10 °C ... 60 °C
- **Product weight**163 g
- **Pneumatic connection 3G1/2**
- **Pneumatic connection 4G1/2**
- **Note on materials**RoHS-compliant
- **Housing material**Die-cast aluminum

