



Pressure switch 061B000466

URL: <https://www.sxplc.com/pressure-switch-061b000466>

Product data sheet

Product details

Gross weight	0.296 Kilogram
Net weight	0.246 Kilogram

Volume	0.641 Liter
EAN	5702423213498

Ambient temperature range [°C] [max]	85 °C
Ambient temperature range [°C] [min]	-40 °C
Ambient temperature range [°F] [max]	185 °F

Ambient temperature range [°F] [min]	-40 °F
Approval	ABS BV CCC CCS CE CMIM DNV EAC GL KRS LLC CDC EURO-TYSK LR LVD NKK RINA RMRS RoHS RoHS China TYSK UKCA
Burst pressure [bar]	30 bar
China RoHS compliance	Yes
Contact function	SPDT
Contact rating	AC15=0.5 A, 250 V DC13=12 W, 125 V
Diff.@Max. range setting [bar]	0.45 bar
Diff.@Min. range setting [bar]	0.3 bar
Electrical conn. Male/Female	Female
Electrical connection	DIN-plug

Electrical connection size	Pg 11
Electrical connection standard	EN 175301-803-A
Electrical spec. standard	EN 60947-5
Enclosure rating IP	IP65
EU RoHS compliance	Out of scope
In scope of WEEE and contain batteries	No
Max. test pressure [bar] Pe	15 bar
Max. test pressure [psig]	218 psig
Max. Working Pressure [bar]	15 bar
Max. Working Pressure [psig]	220 psig
Other RoHS documentation	Saudi Arabia RoHS

Packing format	Multi pack
Pressure connection notes	With flange
Pressure connection size	1/4
Pressure connection standard	ISO 228-1
Pressure connection type	G
Pressure Male/Female	Female
Pressure sensing element	Bellows
Product accessories	Switches accessories
Product description	Pressure Switch
Product group	Switches and thermostats
Product Name Description	Pressure switch
Quantity per packing format	32 pc
REACH Candidate List substances	Lead (CAS no. 7439-92-1)
Regulation range [bar] Pe [max]	4 bar
Regulation range [bar] Pe [min]	-0.2 bar
Regulation range [MPa] Pe [max]	0.4 MPa
Regulation range [MPa] Pe [min]	-0.02 MPa
Reset function	Auto

SCIP dossier no.	c9549e84-c103-45b0-86ec-6021ce3385c8
Serviceable	No
Specification key	1211-1DB04
Type	MBC 5100
UK RoHS compliance	Out of scope

