



## **Push Button, ZB4BA3**

URL:https://www.sxplc.com/push-button-zb4ba3

## **Product data sheet**

Product or Component Type  Device short name  Z	Harmony XB4 Head for non-illuminated push-button ZB4 Chromium plated metal
Device short name	ZB4
Bezel material	Chromium plated metal
Mounting diameter 0	0.9 in (22.5 mm)
Sale per indivisible quantity	1
Head type	Standard
Shape of signaling unit head	Round
Type of operator	Spring return
Operator profile	Green flush, unmarked
Cap/operator or lens colour	Green

Complementary	CAD overall width	1.1 in (29 mm)
	CAD overall height	1.1 in (29 mm)
	CAD overall depth	1.1 in (28 mm)
	Mechanical durability	10000000 cycles
	Electrical composition code	C1 9 single front mounting
		C2 9 single and double front mounting
		C11 3 single front mounting

1/2

	C15 1 single front mounting
device presentation	Basic element

Environment	protective treatment	тн
	Ambient Air Temperature for Storage	-40158 °F (-4070 °C)
	Ambient Air Temperature for Operation	-40158 °F (-4070 °C)
	Overvoltage category	Class I IEC 60536
	IP degree of protection	IP66 IEC 60529
		IP67
		IP69
		IP69K

