



Solenoid Controlled Relief Valve **S-BSG-03-2B3B-D24-N1-L-52T**

URL: <https://www.sxplc.com/solenoid-controlled-relief-valve-s-bsg-03-2b3b-d24-n1-l-52t>

Product data sheet

F-	A-	S-	BS	G	-03	-V	-2B3A	-A100	-N	-L	52	*
Special Seals	With Vent Restrictor	Low Noise Type	Series Number	Type of Mtg.	Valve size	High Venting Pres. Feature	Vent Type	Coil Type	Type of Electrical Connections	Direction of Handle	Design Number	Design Standards
F: Special Seals for Phosphate Ester Type Fluids (Omit if not required)	A: With Vent Restrictor (option)	S: Low Noise Type	BS: Solenoid Controlled Relief Valves	G: Sub-plate Mtg	03	V: For High Venting Pressure Feature (Omit if not required)	2B3A 2B3B 2B2B 2B2 3C2 3C3	AC: A100 A120 A200 A240	None: Terminal Box Type N: With Plug-in Connector (DIN)	(Viewed from pressure gauge Connection) L: Left (Normal) R: Right	52	None: Japanese Std. "JIS" 90: N. American Design Std.
					06			DC: D12 D24 D48				
					10			AC →DC: R100 R200	N: With Plug-in Connector (DIN)	-		80: European Design Std.

