



## Contact block, spring return, front mounting XEN-G1191

URL:<https://www.sxplc.com/contact-block-spring-return-front-mounting-xen-g1191>

**Product data sheet**

<b>Contact block application</b>	2-speed
<b>Contact block type</b>	Single
<b>Type of operator</b>	Spring return
<b>Product Compatibility</b>	XACA XACA9...head
<b>Contacts type and composition</b>	1 NC + 2 NO
<b>Mounting of block</b>	Front mounting
<b>Contact operation</b>	Slow-break Staggered

## Complementary

<b>Connections - terminals</b>	Screw clamp terminals, 1 x 0.5...1 x 2.5 mm <sup>2</sup> without cable end Screw clamp terminals, 1 x 0.5...2 x 1.5 mm <sup>2</sup> with cable end
<b>Mechanical durability</b>	1000000 cycles
<b>Contact code designation</b>	A600 AC-15, U <sub>e</sub> = 240 V, I <sub>e</sub> = 3 A IEC 60947-5-1 appendix A A600 AC-15, U <sub>e</sub> = 600 V, I <sub>e</sub> = 1.2 A IEC 60947-5-1 appendix A Q600 DC-13, U <sub>e</sub> = 250 V, I <sub>e</sub> = 0.27 A IEC 60947-5-1 appendix A Q600 DC-13, U <sub>e</sub> = 600 V, I <sub>e</sub> = 0.1 A IEC 60947-5-1 appendix A
<b>[I<sub>the</sub>] conventional enclosed thermal current</b>	10 A
<b>[U<sub>i</sub>] rated insulation voltage</b>	600 V 3)IEC 60947-1
<b>[U<sub>imp</sub>] rated impulse withstand voltage</b>	6 kV IEC 60947-1
<b>Maximum resistance across terminals</b>	25 MOhm
<b>Operating force</b>	18 N
<b>Short-circuit protection</b>	10 A fuse protection cartridge gG
<b>Rated operational power in W</b>	40 W DC-13 1000000 cycles 60 cyc/mn 120 V 0.5 inductive IEC 60947-5-1 appendix C 48 W DC-13 1000000 cycles 60 cyc/mn 48 V 0.5 inductive IEC 60947-5-1 appendix C 65 W DC-13 1000000 cycles 60 cyc/mn 24 V 0.5 inductive IEC 60947-5-1 appendix C

