



## switching mode power supply **PSSR-VD24**

URL: [https://www.sxplc.com/switching-mode-power-supply-ps5r-  
vd24](https://www.sxplc.com/switching-mode-power-supply-ps5r-<br/>vd24)

### Product data sheet

#### Main Features

Rotary pop-up terminal structure (SS terminal) improves the connection speed of round terminals.

22.5mm (10W/15W/30W), 36mm (60W/90W), 46mm (120W), and 60mm (240W) wide slim type body.

Corresponds to 6 mounting directions.

Can be mounted directly to the panel using the direct mounting kit.

CE compliant. (LVD, EMCD) UL (UL508, UL1310 Class 2 (\*), ANSI/ISA12.12.01), c-UL (CSA C22.2 No. 107.1, 213, 223 (\*)) TÜV SÜD (EN60950-1, EN50178) certified products, EN50178) certified products. \* 1: PSSR-VB/VC/VD/VE type only.

Corresponds to EN61204-3 (DC switching power supply EMC standard Class B).

Corresponds to SEMI F47 standard (at 208V AC input).

Compliant with RoHS directive.

Warranty period: 5 years.

Translated with DeepL.com (free version)

## Product Specifications

### Electrical Specifications

Input Voltage 100-240vac

Output Capacity 60W

### Electrical Specifications (Output Conditions)

Output Voltage 24V DC

