



## Shut-off valve, HE-2-QS-8

URL: <https://www.sxplc.com/shut-off-valve-he-2-qs-8>

### Product data sheet

- |   |
|---|
| • <b>Valve function</b> 2/2 double solenoid   |
| • <b>Pneumatic connection, port 1</b> QS-8  |
| • <b>Pneumatic connection, port 2</b> QS-8  |
| • <b>Type of actuation</b> Manual   |
| • <b>Type of mounting</b> Either: Direct mounting via through-hole In-line installation |
| • <b>Standard nominal flow rate (standardised to DIN 1343)</b> 415.8 l/min              |
| • <b>Nominal size</b> 3.5 mm  |
| • <b>Operating pressure</b> -0.095 MPa ... 1 MPa  |
| • <b>Operating pressure</b> -0.95 bar ... 10 bar  |
| • <b>Ambient temperature</b> 0 °C ... 60 °C   |
| • <b>Material housing</b> PBT-reinforced  |
| • <b>Operating medium</b> Compressed air to ISO 8573-1:2010 [7:-:-]                     |
| • <b>Sealing principle</b> Soft   |

- **Mounting position** optional
- **Design** Piston gate valve
- **Type of piloting** Direct
- **Flow direction** Reversible
- **Symbol** 00997328
- **Note on operating and pilot medium** Lubricated operation possible  
(in which case lubricated operation will always be required)
- **Corrosion resistance class** CRC2 - Moderate corrosion stress
- **LABS (PWIS) conformity** VDMA24364-B1/B2-L
- **Cleanroom class** Class 4 according to ISO 14644-1
- **Media temperature** 0 °C ... 60 °C
- **Product weight** 26 g
- **Note on materials** RoHS-compliant
- **Material seals** NBR

