



Solenoid coil,018F6730

URL:<https://www.sxplc.com/solenoid-coil-018f6730>

Product data sheet

Gross weight	0.334 Kilogram
Net weight	0.305 Kilogram

Volume	0.319 Liter
EAN	5702428023139

Actuator size	13.5 mm
Ambient temperature range [°C] [max]	50 °C

Ambient temperature range [°C] [min]	-40 °C
Ambient temperature range [°F] [Max]	120 °F
Ambient temperature range [°F] [Min]	-40 °F
Approval	LLC CDC TYSK CE EAC UKCA
Cable diameter [mm] [Max]	11 mm
Cable diameter [mm] [Min]	6 mm
China RoHS compliance	Out of scope
Coil connection	Connection box
Coil design standard	VDE 0580
Coil fastening	Clip-on
Coil winding insulation class	Class H to IEC 85
Colour	Blue
Compliance	EN 60730-1
Conductor area [mm ²]	0.75 - 1.5 mm ²
Duty rating	Continuous
EEE category	5 small equipment (any external dimension 50 cm)?
Electrical connection	Terminal box
Electrical connection size	Pg 13.5
Enclosure rating IP	IP67
EU RoHS compliance	Out of scope
Frequency [Hz]	50/60 Hz
Identical product	018F8730
In scope of WEEE	Yes
In scope of WEEE and contain batteries	No
Packing format	Multi pack

	EV251B
Power consumption 50Hz [VA]	EV220B
Power consumption 60Hz [VA]	EV222B
Power consumption [W] 50Hz	EV220B W5 - 50
Power consumption [W] 60Hz	EV222B W6 - 22
Product accessories	Solenoid coils accessories
Product group	Solenoid valves
Product Name Description	Steel coil
REACH Candidate List substances	Lead (CAS 7439-92-1)
Rel. Humidity [% RH] [Max]	EV250B
Rel. Humidity [% RH] [min]	0 %
SCIP dossier no.	23785618-b379-4da7-a913-eed40c8fae6d
SCIP dossier product name	Solenoid coils
Serviceable	No
Spare part number	018F6192
Supply voltage 50Hz Max [V]	110 V
Supply voltage 60Hz Max [V]	110 V
Supply voltage [V] AC	110 V
Type	BE110CS
Type designation	BE110CS
UK RoHS compliance	Out of scope

