



## Pressure switch-061B201266

URL: <https://www.sxplc.com/pressure-switch-061b201266>

### Product data sheet

Alarm Signal	Falling
Ambient temperature range [°C] [max]	85 °C
Ambient temperature range [°C] [min]	-40 °C
Ambient temperature range [°F] [max]	185 °F
Ambient temperature range [°F] [min]	-40 °F
Approval	CCC CE EAC LLC CDC EURO-TYSK LVD RoHS RoHS China UKCA
Burst pressure [bar]	30 bar
China RoHS compliance	Yes
Contact function	SPDT
Contact rating	AC15=0.5 A, 250 V DC13=12 W, 125 V
Diff.@Max. range setting [bar]	0.45 bar
Diff.@Min. range setting [bar]	0.3 bar
Electrical conn. Male/Female	Female

Electrical connection	DIN-plug
Electrical connection size	Pg 11
Electrical connection standard	EN 175301-803-A
Electrical spec. standard	EN 60947-5
Enclosure rating IP	IP65
EU RoHS compliance	Out of scope
Factory setting [bar]	0.5 bar
Factory setting [MPa]	0.05 MPa
In scope of WEEE and contain batteries	No
Max. test pressure [bar] Pe	15 bar
Max. test pressure [psig]	218 psig
Max. Working Pressure [bar]	15 bar

Max. Working Pressure [psig]	220 psig
Other RoHS documentation	Saudi Arabia RoHS
Packing format	Multi pack
Pressure connection size	1/4
Pressure connection standard	ISO 228-1
Pressure connection type	G
Pressure Male/Female	Female
Pressure sensing element	Bellows
Product accessories	Switches accessories
Product description	Pressure Switch
Product group	Switches and thermostats
Product Name Description	Pressure switch
Quantity per packing format	32 pc
REACH Candidate List substances	Lead (CAS no. 7439-92-1)
Regulation range [bar] Pe [max]	1 bar
Regulation range [bar] Pe [min]	-0.2 bar
Regulation range [MPa] Pe [max]	0.1 MPa
Regulation range [MPa] Pe [min]	-0.02 MPa
Reset function	Auto
SCIP dossier no.	c9549e84-c103-45b0-86ec-6021ce3385c8
Serviceable	No
Specification key	1011-1CB04
Type	MBC 5000

UK RoHS compliance	Out of scope

