



BREAKER, Type: XT2S 160 TMA
160-1600 3p F F,Product ID:
1SDA067560R1

URL:<https://www.sxplc.com/breaker-type->

[xt2s-160-tma-160-1600-3p-f-f-product-id-1sda067560r1](https://www.sxplc.com/breaker-type-xt2s-160-tma-160-1600-3p-f-f-product-id-1sda067560r1)

Product data sheet

Circuit Breaker Type to be Associated:

Power Distribution

Connecting Capacity Main Circuit:

Busbar 32.5..100 mm²

Current Type:

AC/DC

Electrical Durability:

120 cycles per hour

8000 cycle



Mechanical Durability:

240 cycles per hour

25000 cycle

Number of Poles:

3

Opening Time:

CB with SOR 15 ms

CB with UVR 15 ms



Order Multiple:

1 piece

Power Loss:

at Rated Operating Conditions per Pole 16.15 W

Product Main Type:

SACE Tmax XT

Product Name:

Moulded Case Circuit Breaker

Product Type:

Automatic Circuit Breaker

Rated Current (In):

160 A

Rated Frequency (f):

50 / 60 Hz

Rated Voltage (U_r):

690 V

Rated Impulse Withstand Voltage (U_{imp}):

8 kV

Rated Instantaneous Short-Circuit Current Setting (I_i):

800...1600 A

Rated Insulation Voltage (U_i):

1000 V



Rated Operational Voltage:

690 V AC

500 V DC

