



## **BREAKER,XT3N 250 TMD 200-2000**

### **3p F F, 1SDA068058R1**

URL:<https://www.sxplc.com/breaker-xt3n-250-tmd-200-2000-3p-f-f-1sda068058r1>

## **Product data sheet**

Circuit Breaker Type to be Associated:

Power Distribution

---

Connecting Capacity Main Circuit:

Busbar 85..192 mm<sup>2</sup>

---

Current Type:

AC/DC

---

Electrical Durability:

120 cycles per hour

8000 cycle



Mechanical Durability:

240 cycles per hour

25000 cycle



Number of Poles:

3



Opening Time:

CB with SOR 15 ms

CB with UVR 15 ms



Order Multiple:

1 piece

---

Power Loss:

at Rated Operating Conditions per Pole 13.2 W

---

Product Main Type:

SACE Tmax XT

---



Product Name:

Moulded Case Circuit Breaker

---

Product Type:

# Automatic Circuit Breaker

---

Rated Current ( $I_n$ ):

200 A

---

Rated Frequency (f):

50 / 60 Hz

---

Rated Voltage ( $U_r$ ):

690 V

---

Rated Impulse Withstand Voltage ( $U_{imp}$ ):

8 kV

---

Rated Instantaneous Short-Circuit Current Setting ( $I_i$ ):

2000 A

---

Rated Insulation Voltage ( $U_i$ ):

800 V

---

Rated Operational Voltage:

690 V AC

500 V DC

