

BREAKER,XT3N 250 TMD 200-2000

3p F F, 1SDA068058R1

URL:<https://www.sxplc.com/breaker-xt3n-250-tmd-200-2000-3p-f-f-1sda068058r1>

Product data sheet

Circuit Breaker Type to be Associated:

Power Distribution

Connecting Capacity Main Circuit:

Busbar 85..192 mm²

Current Type:

AC/DC

Electrical Durability:

120 cycles per hour

8000 cycle



Mechanical Durability:

240 cycles per hour

25000 cycle



Number of Poles:

3



Opening Time:

CB with SOR 15 ms

CB with UVR 15 ms



Order Multiple:

1 piece

Power Loss:

at Rated Operating Conditions per Pole 13.2 W

Product Main Type:

SACE Tmax XT

Product Name:

Moulded Case Circuit Breaker

Product Type:

Automatic Circuit Breaker

Rated Current (In):

200 A

Rated Frequency (f):

50 / 60 Hz

Rated Voltage (U_r):

690 V

Rated Impulse Withstand Voltage (U_{imp}):

8 kV

Rated Instantaneous Short-Circuit Current Setting (I_i):

2000 A

Rated Insulation Voltage (U_i):

800 V

Rated Operational Voltage:

690 V AC

500 V DC

