



Level control relay RM22LG11MR

URL:https://www.sxplc.com/level-control-relay-rm22lg11mr

Product data sheet

Range of product	Harmony Control Relays	
Relay type	Level control relay	
product or component type	Level control relay	
Relay name	RM22L	
Relay monitored parameters	Detection by resistive probes	
time delay	Without	
Switching capacity in VA	2000 VA	
Minimum switching current	10 mA at 5 V DC	
Maximum switching current	8 A AC	
Utilisation category	AC-15 conforming to IEC 60947-5-1	
	DC-13 conforming to IEC 60947-5-1	
	AC-1 conforming to IEC 60947-4-1	
	DC-1 conforming to IEC 60947-4-1	
Contacts type and composition	2 C/O	

Complementary	Maximum switching voltage	250 V AC
	[Un] rated nominal voltage	24240 V AC/DC 50/60 Hz, non self-powered
	Supply voltage limits	20.4264 V AC/DC
	power consumption	1.5 W DC

Output contacts	2 C/O
Nominal output current	8 A
delay at power up	0.6 s
Maximum electrode voltage	12 V AC
Maximum electrode current	1 mA
Repeat accuracy	+/- 2 % for time delay
Measurement error	< 1 $\%$ over the whole range with voltage variation
	0.05 %/°C with temperature variation
Maximum cable distance between	1000 m between probe and delay
devices	
Sensitivity scale	5100 kOhm St (Standard Sensitivity)
Sensitivity adjustment	5100 %
Maximum supply current for sensors	1 mA
Cable capacitance	1 nF at HS (High Sensitivity) for probe cable
	2.2 nF at St (Standard Sensitivity) for probe cable
	4.7 nF at LS (Low Sensitivity) for probe cable
Overvoltage category	III conforming to IEC 60664-1
Insulation	Between supply and measurement
Connections - terminals	Screw terminals, 2 x 0.52 x 2.5 mm ² (AWG 20AWG
	without cable end
	Screw terminals, 2 x 0.22 x 1.5 mm ² (AWG 24AWG
	flexible with cable end
	Screw terminals, 1 x 0.51 x 3.3 mm ² (AWG 20AWG
	without cable end
	Screw terminals, 1 x 0.21 x 2.5 mm ² (AWG 24AWG
	flexible with cable end
Tightening torque	0.61 N.m conforming to IEC 60947-1
Housing material	Self-extinguishing plastic
Mounting support	35 mm DIN rail conforming to IEC 60715
Mounting position	Any position

Electrical durability	100000 cycles
Mechanical durability	1000000 cycles
Contacts material	Cadmium free
Measurement range	5100 kOhm
Safety reliability data	B10d = 120000
	MTTFd = 125.5 years
Width	22.5 mm
Control type	With test button
net weight	0.1 kg

