



Pressure switch-017-520366

URL:<https://www.sxplc.com/pressure-switch-017-520366>

Product data sheet

Product details

Gross weight	0.984 Kilogram
Net weight	0.888 Kilogram

Volume	2.726 Liter
EAN	5702423120604

Ambient temperature range [°C] [max]	70 °C
Ambient temperature range [°C] [min]	-50 °C
Ambient temperature range [°F] [max]	158 °F

Ambient temperature range [°F] [min]	-58 °F
Approval	BV CCC CE CMIM DNV EAC GL KR LLC CDC EURO-TYSK LR LVD NKK PZH RINA RMRS RoHS RoHS China TYSK UKCA
China RoHS compliance	Yes
Contact function	SPDT
Contact rating	AC15=3 A, 400 V AC1=10 A, 400 V AC3=4 A, 400 V DC13=12 W, 220 V LR=28 A, 400 V
Differential [bar] [max]	1.3 bar
Differential [bar] [min]	0.33 bar
Differential [psi] [max]	18.9 psi
Differential [psi] [min]	4.8 psi
EEE category	5 small equipment (any external dimension 50 cm)?
Electrical conn. Male/Female	Female
Electrical connection	Screwed cable entry
Electrical connection size	2xPg 13.5
Electrical connection standard	DIN 40430
Electrical spec. standard	EN 60947-4/-5

	Pollution degree: 3
	Rated impulse voltage: 4 kV
	Short circuit prot, fuse: 10A
EN 60977 wiring properties	Flex, ferrules: 0.2-0.5 mm ²
	Flex, no ferrules: 0.2-2.5 mm ²
	Solid/stranded: 0.2-2.5 mm ²
Enclosure rating IP	IP66
EU RoHS compliance	Yes
EU RoHS exemption clause	No
In scope of WEEE	Yes
In scope of WEEE and contain batteries	No

