



**□LE1M35Q712□ Enclosed DOL
starter, TeSys LE,3.7-5.5A, 380V AC
coil, including 1 LC1K,LR2K,2
pushbuttons, yellow indicator, 60
HZ.**

URL:<https://www.sxplc.com/le1m35q712-enclosed-dol-starter-tesys-le-3-7-5-5a-380v-ac-coil-including-1-lc1k-lr2k-2-pushbuttons-yellow-indicator-60-hz>

Product data sheet

Thermal protection adjustment range

3.7...5.5 A

Motor power kW

0.75 kW at 240 V AC 50/60 Hz

2.2 kW at 415 V AC 50/60 Hz

1.1 kW at 220/230 V AC 50/60 Hz

2.2 kW at 380/400 V AC 50/60 Hz

[Uc] control circuit voltage

380 V AC 50/60 Hz

Control type

Push-button start green I

Push-button stop/reset red O

Complementary

Local signalling

Operating: LED (yellow)

Cable entry number

2 ISO20 top

2 ISO25 top

2 Pg 13 top

2 Pg 21 top

2 ISO20 bottom

2 ISO25 bottom

2 Pg 13 bottom

2 Pg 21 bottom

2 Pg 16 top

2 Pg 16 bottom

Width

78 mm

Height

160 mm

Depth

108 mm

net weight

0.6 kg

Environment

Material

ABS (acrylonitrile butadiene-styrene)

IP degree of protection

IP65 conforming to IEC 60529

Standards

IEC 60947-4-1

Ambient air temperature for operation

-5...40 °C

Environmental characteristic

Standard environment

Product certifications

UKCA

Packing Units

Unit Type of Package 1

PCE

Number of Units in Package 1

1

Package 1 Height

11.600 cm

Package 1 Width

16.600 cm

Package 1 Length

8.200 cm

Package 1 Weight

572.900 g

Unit Type of Package 2

S02

Number of Units in Package 2

6

Package 2 Height

15.000 cm

Package 2 Width

30.000 cm

Package 2 Length

40.000 cm

Package 2 Weight

3.766 kg

Unit Type of Package 3

P06

Number of Units in Package 3

96

Package 3 Height

75.000 cm

Package 3 Width

60.000 cm

Package 3 Length

80.000 cm

Package 3 Weight

70.788 kg

Contractual warranty

Warranty

18 months

