



Head for push button XACA9413

URL: <https://www.sxplc.com/head-for-push-button-xaca9413>

Product data sheet

Marking	Unmarked
Operator additional information	Booted
Cap/operator or lens colour	Green
Product compatibility	XACA..
mounting location	Front of enclosure
Sale per indivisible quantity	10
Standards	IEC 60947-5-1 CSA C22.2 No 14 UL 508 IEC 60204-32
Ambient air temperature for operation	-25...70 °C
ambient air temperature for storage	-40...70 °C
Vibration resistance	15 gn (f= 10...500 Hz) conforming to IEC 60068-2-6
Shock resistance	100 gn conforming to IEC 60068-2-27
Overvoltage category	Class II conforming to IEC 61140
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK08 conforming to IEC 62262
Net weight	0.01 kg

Packing Units	Unit Type of Package 1	PCE
	Number of Units in Package 1	1
	Package 1 Height	3.0 cm
	Package 1 Width	14.0 cm
	Package 1 Length	17.0 cm
	Package 1 Weight	9.0 g
	Unit Type of Package 2	BAG
	Number of Units in Package 2	10
	Package 2 Height	3.0 cm
	Package 2 Width	7.5 cm
	Package 2 Length	11.0 cm
	Package 2 Weight	94.0 g
	Unit Type of Package 3	S03
	Number of Units in Package 3	700
	Package 3 Height	30.0 cm
	Package 3 Width	30.0 cm
	Package 3 Length	40.0 cm
	Package 3 Weight	7.068 kg

