



## socket RXZE2M114

URL: <https://www.sxplc.com/socket-rxze2m114>

### Product data sheet

Shape of pin	Flat
[Ue] rated operational voltage	< 250 V conforming to IEC < 300 V conforming to UL
Contact terminal arrangement	Mixed
Connections - terminals	Screw clamp terminals, 1 x 0.25...1 x 1 mm <sup>2</sup> (AWG 22...AWG 17) flexible with cable end Screw clamp terminals, 2 x 0.25...2 x 1 mm <sup>2</sup> (AWG 22...AWG 17) flexible with cable end Screw clamp terminals, 1 x 0.5...1 x 1.5 mm <sup>2</sup> (AWG 20...AWG 16) solid without cable end Screw clamp terminals, 2 x 0.5...2 x 1.5 mm <sup>2</sup> (AWG 20...AWG 16) solid without cable end
Tightening torque	< 1 N.m for M3 screw(s)
Fixing mode	By screw (panel) Clip-on (35 mm symmetrical DIN rail)
[Uimp] rated impulse withstand voltage	4 kV
Overvoltage category	III
Pollution degree	3
Sale per indivisible quantity	10
Width	30 mm

Net weight	0.048 kg
------------	----------

Environment	IP degree of protection	IP20 conforming to IEC 60529
	Dielectric strength	2500 V
	Standards	IEC 61984
	Product certifications	UL
		CSA
		Lloyd's
	Marking	CE
	ambient air temperature for storage	-40...85 °C
Ambient air temperature for operation	-40...55 °C	

Packing Units	Unit Type of Package 1	PCE
	Number of Units in Package 1	1
	Package 1 Height	3.896 cm
	Package 1 Width	3.005 cm
	Package 1 Length	8.218 cm
	Package 1 Weight	52.0 g
	Unit Type of Package 2	BB1
	Number of Units in Package 2	10
	Package 2 Height	7.4 cm
	Package 2 Width	8.8 cm
	Package 2 Length	15.0 cm
	Package 2 Weight	0.621 kg
	Unit Type of Package 3	S03
	Number of Units in Package 3	200
	Package 3 Height	30.0 cm
	Package 3 Width	30.0 cm

Package 3 Length	40.0 cm
Package 3 Weight	11.851 kg

---

