



**Hand slide valve,  
VBOH-32-G14,1302994**

URL:<https://www.sxplc.com/hand-slide-valve-vboh-32-g14-1302994>

**Product data sheet**

- |  |
|--|
| • <b>Valve function</b> 3/2 double solenoid                                  |
| • <b>Pneumatic connection, port 1</b> G1/4                                   |
| • <b>Pneumatic connection, port 2</b> G1/4                                   |
| • <b>Type of actuation</b> Manual  |
| • <b>Type of mounting</b> In-line installation Screw-in                      |
| • <b>Standard nominal flow rate (standardised to DIN 1343)</b> 1675<br>l/min |
| • <b>Nominal size</b> 8.4 mm   |
| • <b>Operating pressure</b> -0.095 MPa ... 1.2 MPa                           |
| • <b>Operating pressure</b> -0.95 bar ... 12 bar                             |
| • <b>Ambient temperature</b> -10 °C ... 80 °C                                |
| • <b>Material housing</b> Anodised wrought aluminium alloy                   |
| • <b>Operating medium</b> Compressed air to ISO 8573-1:2010 [7:4:4]          |
| • <b>Grid dimension</b> 31 mm  |

- **Instructions on use** Bitte nur Verschraubungen mit zylindrischem Gewinde einschrauben. Die Montage von konischem Gewinde kann das Gehäuse beschädigen und somit eine Klemmung bzw. Fehlfunktionen der Hülse verursachen.
- **Sealing principle** Soft
- **Mounting position** optional
- **Design** Sleeve valve
- **Type of piloting** Direct
- **Flow direction** Reversible
- **Symbol** 00991286
- **Note on operating and pilot medium** Lubricated operation possible (in which case lubricated operation will always be required)
- **Corrosion resistance class** CRC2 - Moderate corrosion stress
- **LABS (PWIS) conformity** VDMA24364-B2-L
- **Media temperature** -10 °C ... 80 °C
- **Actuating force** 45 N
- **Product weight** 35 g
- **Material screwed plug** Anodised wrought aluminium alloy
- **Note on materials** RoHS-compliant
- **Material seals** NBR

