



## Switched-mode power supply

### 787-740

URL: <https://www.sxplc.com/switched-mode-power-supply-787-740>

## Product data sheet

## Output

Nominal output voltage $U_{o\ nom}$	DC 24 V (SELV)
Output voltage range	DC 22 ... 28 V (adjustable)
Default setting	DC 24 V
Nominal output current $I_{o\ nom}$	10 A (24 VDC)
Nominal output power	240 W
Control deviation	$\leq 1\ %$
Residual ripple	$\leq 100\ mV$ (peak-to-peak)
Overload behavior	Constant power (in overload range: $1.15 \dots 1.4 \times I_{o\ nom}$ ); Shutdown and automatic restart in the event of a short circuit

## Signaling and communication

Signaling	1 x LED DC OK (green) 1 x Overload LED (red) 1 x DC OK signal output (optocoupler as make contact; max. 31.2 V; 20 mA)
Operation status indicator	Green LED ( $U_o$ ) Red LED (overload)

## Efficiency/power losses

Power loss $P_l$	$\leq 32.5\ W$
Power loss (max.) $P_{l\ (max)}$	36 W
Efficiency (typ.)	89 %

## Circuit protection

Internal fuse	3 x T 2 A / 250 VAC
Required backup fusing	An external DC fuse is required for the DC input voltage.
Recommended backup fusing	3 x circuit breaker $\geq 6\ A$ ; Tripping characteristic: B or C Alternative: motor circuit breaker

## Safety and protection

Isolation voltage (Pri.-Sec.)	DC 4.242 kV
Isolation voltage (Pri.-GND)	DC 2.2 kV

