



Connection

lead-7000-12421-614-1000

URL: [https://www.sxplc.com/connection-](https://www.sxplc.com/connection-lead-7000-12421-614-1000)

lead-7000-12421-614-1000

Product data sheet

Thread	M12	
Number of pins	4	
Connector variant	angled	
Cable length	10m	
Connector	plug	
Max. operating current	4A	
Operating temperature	-30...80°C	
Wire insulation material	PVC	
Skrót		Pełna nazwa
CR		Neoprene
ETFE		Ethylene Tetrafluoroethylene
EPDM		Ethylene Propylene Diene Monomer

FEP	Fluoroethylene Butylene
FHDPE	High-Density Polyethylene
FRNC	Fire Resistant Non-Corrosive
HDPE	High-Density Polyethylene
LSZH	Low Smoke Zero Halogen
MPPE	Modified Polyphenylene Ether
PA	Polyamide
PE	Polyethylene
PFA	Perfluoroalkoxy
PO	Polyolefine
PPO	Polyphenylene oxide
PTFE	Polytetrafluoroethylene
PUR	Polyurethane
PVC	Polyvinyl Chloride
PVC FirestoP®	Fire Retardant Polyvinyl Chloride
PVC TM2	Polyvinyl Chloride, Thermoplastic, Medium Impact
PVDF	Polyvinylidene Fluoride
SBR	Styrene Butadiene Rubber
THHN	Thermoplastic, High Heat-Resistant, Nylon-Coated
TPE	Thermoplastic Elastomer
TPE-S	Thermoplastic Elastomer Styrenic
TPE-U	Thermoplastic Elastomer Urethane
VMQ	Silicone Caoutchouc
XLPE	Cross-Linked Polyethylene
XLPE	Cross-Linked Copolymer
X-FRNC	Cross-Linked Flame Retardant Non- Corrosive

IP rating	IP67	
Insulation colour	grey	
Kind of connector	female	
Indication	LED	
Max. operating voltage	24V DC	

