Solenoid valve ,MFH-5-1/2,6420

URL:https://www.sxplc.com/solenoid-valve-mfh-5-1-2-6420

Product data sheet

- Valve function5/2-way, monostable
- Type of actuationElectric
- Construction width52 mm
- Standard nominal flow rate (standardised to DIN 1343)3700
- pneumatic working portG1/2
- **Operating voltage**Via solenoid coil, must be ordered separately
- Operating pressure 0.2 MPa ... 0.8 MPa
- Operating pressure2 bar ... 8 bar
- **Design**Poppet seat
- Type of resetMechanical spring
- **Approval**c UL us Recognized (OL)
- Degree of protection IP65
- Nominal size14 mm
- Grid dimension 69 mm

- Exhaust-air functionWith flow control option
- Sealing principleSoft
- Mounting position
 optional
- Manual override Detenting
- Type of pilotingPilot actuated
- Flow directionNon-reversible
- Symbol00991035
- lapUnderlap
- **b value**0.32
- Switching time off150 ms
- Switching time on21 ms
- Max. positive test pulse with 0 signal 2200 μs
- Max. negative test pulse with 1 signal $3700 \ \mu s$
- Characteristic coil dataSee solenoid coil, to be ordered separately
- **Operating medium**Compressed air to ISO 8573-1:2010 [7:4:4]
- Note on operating and pilot mediumLubricated operation possible

(in which case lubricated operation will always be required)

- Corrosion resistance class CRC1 Low corrosion stress
- LABS (PWIS) conformityVDMA24364-B1/B2-L
- Storage temperature-20 °C ... 60 °C
- Media temperature-10 °C ... 60 °C
- Ambient temperature-5 °C ... 40 °C
- Product weight1135 g

- **Electrical connection**Via F coil, to be ordered separately
- **Type of mounting**Either: On manifold rail With through-hole
- Pilot exhaust port 84M5
- Pneumatic connection, port 1G1/2
- Pneumatic connection, port 2G1/2
- Pneumatic connection, port 3G1/2
- Pneumatic connection, port 4G1/2
- Pneumatic connection, port 5G1/2
- Note on materialsRoHS-compliant
- Material sealsNBR TPE-U(PU)
- Material housingDie-cast aluminium

