



## Safety controllers: Flexi Classic

**UE410-4RO3 Part no.: 6026143**

URL: <https://www.sxplc.com/safety-controllers-flexi-classic-ue410-4ro3-part-no-6026143>

**Product data sheet**

<b>Module</b>	Relay module
<b>Configuration method</b>	Hard wired

### Safety-related parameters

<b>Safety integrity level</b>	SIL 3 (IEC 61508)
<b>Category</b>	Category 4 (EN ISO 13849)
<b>Performance level</b>	PL e (EN ISO 13849)

### Interfaces

<b>Outputs</b>	4 enabling current paths
<b>Number of control inputs</b>	2 (B1, B2)
<b>Number of enable current contacts</b>	4 (13/14, 23/24, 33/34, 43/44)
<b>Number of signaling current paths</b>	2 (Y14, Y24)
<b>Number of signaling current contacts</b>	2 (Y1/Y2, Y3/Y4)
<b>Connection type</b>	Plug-in screw-type terminals
<b>Display elements</b>	LEDs

### Electrical data

<b>Protection class</b>	III (EN 61140)
<b>Voltage supply</b>	Via FLEXBUS+
<b>Power consumption</b>	≤ 3.2 W
<b>Internal power consumption</b>	≤ 3.2 W <sup>1)</sup>
<b>Overvoltage category</b>	II (EN 61131-2)
<b>Switching inputs</b>	
Terminals	B1, B2
Input voltage	18 V DC ... 30 V DC

