



## Bearing 6052-M-C3

URL: <https://www.sxplc.com/bearing-6052-m-c3>

### Product data sheet

Weight and Dimensions

- Inner (d) MM260
- Outer (D) MM400
- Width (B) MM65
- Inner (d) Inch10.2362
- Outer (D) Inch15.748
- Width (B) Inch2.5591
- Weight (kg)29.6

Product Properties

- BoreC - Cylindrical Bore
- SealNo Seal
- Cage TypeM - Brass Cage
- External ModificationNo External Modification
- Radial Internal PlayC3 Internal Play (Higher than Cn)
- PrecisionStandard Precision
- LubricationStandard Lubrication
- Heat StabilizationNo Heat Stabilization - Temperatures up to 120 °C

- Special TreatmentNo Special Treatment

- Width (b) mm65
- Radial Static Load Rating C<sub>0r</sub> (N)405000
- Radial Dynamic Load Rating C<sub>r</sub> (N)310000
- Basic static load rating, radial (C<sub>0r</sub>)"405000.0000"
- Limiting speed (n G)2750
- Reference speed (n  $\theta$ r)2250
- ECLASS number23-05-08-01
- ECLASS2 number23-05-08-01
- Medias descriptionDeep groove ball bearing 60..-M, single row, cf. DIN 625-1

