

Depth	
Depth (inches)	
Width	
Width (inches)	
Length	
Length (inches)	
Net weight	
Temperatures	
Storage temperature	
Operating temperature	
Probability of failure	
MTTF	
Environmental Product Compliance	
REACH SVHC	
SCIP	
RoHS Compliance Status	
RoHS Exemption (if applicable/known)	
Input	
Line resistance in measuring circuit	
Number of inputs	
Sensor	
Temperature input range	Configurable
Output	
Fine adjustment	? ± 5 %, Vers
Load impedance current	

Number of outputs	
Offset current	
Offset voltage	
Output current	
Output voltage, note	
Wire break detection	LE
load impedance voltage	
Output (digital)	
Status indicator	Module active
General data	
Accuracy	
Configuration	
Galvanic isolation	
Linearity	
Power consumption	
Protection degree	
Rail	
Step response time	fast/slow: 2-/
Temperature coefficient	
Insulation coordination	
EMC standards	
Galvanic isolation	
Impulse withstand voltage	
Insulation voltage	
Insulation voltage input or output/rail	
Insulation voltage input or output/supply	
Pollution severity	

Rated voltage

Surge voltage category

Connection data



Type of connection

Stripping length, rated connection

Tightening torque, min.

Tightening torque, max.

RTD isolating transformer,

Clamping range, rated connection

Clamping range, min.

8560700000

Clamping range, max.



URL:<https://www.sxplc.com/rtd-isolating-transformer-8560700000>

Product data sheet

General ordering data

Version

RTD isolating transformer, 2-



Order No.

Type

GTIN (EAN)

Qty.

Available until

Alternative product