



Connector ACP15034CD

URL:<https://www.sxplc.com/connector-acp15034cd>

Product data sheet

Specifications

Hazardous Area Classification

EBR Receptacle: Class I, Division 1 and 2, Groups B, C, D Class II,
Division 1 and 2, Groups F, G Class III NEMA 3, 3R, 4, 4X, 7CD, 9FG?DBR
Receptacle: Class II, Division 1 and 2, Groups F, G Class III NEMA 3, 3R,
4, 4X, 9FG

Amperage

30, 60, 100 or 150

Voltage

120/240/480/600 Vac or 250 Vdc

Number of Poles

3 or 4

Number of Wires

2 or 3

Horsepower Ratings

1, 1.5, 2, 3, 5, 7.5, 10, 15, 20, 25, 30, 40, 50, 60 or 75

Plug Cable Diameter

30 Amp: 0.500 to 1.125#8221;; 60 Amp: 0.500 to 1.375#8221;; 100 Amp: 0.875 to 1.906#8221;; 150 Amp: 1.09#8221; to 2.187#8221;

Mounting Box Entries

Feed-Thru

Materials and Finishes

Receptacles, mounting box, covers and plug housings are copperfree (4/10 of 1% max.) aluminum with epoxy powder coat. Insulating blocks are fiber glass reinforced polyester.

