



Return Filter RAF0160F010NB16EN

URL: <https://www.sxplc.com/return-filter-raf0160f010nb16en>

Product data sheet

性能参数 Specifications

结构形式: 油箱顶置	Type of construction: Tank top mounted
工作压力: 最大10bar	Operating pressure: Max. 10bar
连接形式: BSPP/公制螺纹, SAE法兰	Connections: Threaded BSPP/Metric, SAE Flange
密封材料: 丁晴橡胶, 氟橡胶	Seal material: NBR, Viton, EPDM on request
工作温度: -30℃ ~ +110℃	Operating temperature range: -30℃ to +110℃
过滤材料: 玻纤, 编织网	Filtration media: Glass fibre, wire mesh
滤芯爆破压力: 10bar	Element collapse rating: 10 bar (ISO 2941)
旁通阀开启压力:	Bypass setting:
0040, 0063, 0120, 0160, 0180, 0220-2.5bar	0040, 0063, 0120, 0160, 0180, 0220-2.5bar
0250, 0330, 0500, 1000-3bar	0160, 0250, 0500, 1000-3bar
发讯器报警压力:	Indicator setting:
0040, 0063, 0120, 0160, 0180, 0220-1.5 bar	0040, 0063, 0120, 0160, 0180, 0220-1.5bar
0250, 0330, 0500, 1000-2.5bar	0160, 0250, 0500, 1000-2.5bar
壳体材料: 铝, 尼龙	Filter housing: Aluminium and PA66
工作介质相容性:	Fluid compatibility: Suitable for mineral oils,
适用于矿物油, 人工合成油,	synthetic oils. For use with water,
其它介质咨询公司技术部门。	please contact our company.

