



breaker 3VA2463-5HM32-0AA0

URL: <https://www.sxplc.com/breaker-3va2463-5hm32-0aa0>

Product data sheet

Product	
Article Number (Market Facing Number)	3VA2463-5HM32-0AA0
Product Description	circuit breaker 3VA2 IEC Frame 630 breaking capacity class M Icu=55 kA @ 415 V 3-pole, line protection ETU330, LIG, In=630 A overload protection Ir=250 A...630 A short-circuit protection li=1.5...9x In ground-fault protection Ig=0.2...1 x In, tg=0.1/0.3s nut keeper kit
Product family	<u>3VA Molded Case Circuit Breakers up to 1600 A. IEC</u>
Product Lifecycle (PLM)	PM300:Active Product
Price data	
Region Specific PriceGroup / Headquarter Price Group	12P / 1CB
List Price	Show prices
Customer Price	Show prices
Surcharge for Raw Materials	None
Metal Factor	LOA-----
Delivery information	
Export Control Regulations	AL : N / ECCN : 9N9999
Estimated dispatch time (Working Days)	5 Day/Days
Net Weight (kg)	5,186 Kg
Packaging Dimension	165,00 x 265,00 x 170,00

Package size unit of measure	MM
Quantity Unit	1 Piece
Packaging Quantity	1
Additional Product Information	
EAN	4042948807682
UPC	804766432392
Commodity Code	85362090
LKZ_FDB/ CatalogID	LV10.1
Product Group	5374
Group Code	P360
Country of origin	Czech Republic
Compliance with the substance restrictions according to RoHS directive	Since: 01.04.2014
Product class	C: products manufactured / produced to order, which cannot be reused or re-utilised or be returned against credit.
WEEE (2012/19/EU) Take-Back Obligation	Yes
REACH Art. 33 Duty to inform according to the current list of candidates	<u>Lead CAS-No. 7439-92-1 > 0, 1 % (w / w)</u> <hr/> <u>Lead monoxide (lead ... CAS-No. 1317-36-8 > 0, 1 % (w / w)</u> <hr/> <u>Silicic acid, lead s... CAS-No. 11120-22-2 > 0, 1 % (w / w)</u>
SCIP number	3cf93ab0-91f4-46cf-881d-1b2e4d32ba65

