



## **BUTTON XB4BA42**

URL:<https://www.sxplc.com/button-xb4ba42>

### **Product data sheet**

Mounting diameter 22.5 mm

Quantity sold separately 1 each

Signal unit head shape Round

Type of operating head Spring return

Joystick shape red Flat head, unmarked

Joystick type Standard

Contact type 1NC

Contact action Slow break

Wiring capacity Screw fastening,  $\leq 2 \times 1.5 \text{ mm}^2$  with terminal blocks according to IEC 60947-1

Bolt-on, 1 x 0.22.... .2 x 2.5 mm<sup>2</sup> without terminal block in accordance with IEC 60947-1

Height 47 mm

Width 30 mm

Depth 52 mm

ISO n°1 terminal (21-22)NC

Net weight 0.08 kg

High-voltage gasket impedance 7000000 Pa at ... 55 °C, distance: 0.1 m

Use of contact wires Standard contacts

Forced open Yes in accordance with IEC 60947-5-1 Appendix K

Operational spread 1.5 mm (NC change of electrical status)

4.3 mm (total travel)

Control force 3.5 N NC change of electrical status

Mechanical life 10000000 cycles

Tightening torque 0.8...1.2 N.m in accordance with IEC 60947-5-1 Appendix K

