



Aluminum Pumps H25AB2D

URL:<https://www.sxplc.com/aluminum-pumps-h25ab2d>

Product data sheet

Maks. fortrængning:	2.227 inch ³ /rev, 36.5 cm ³ /rev
Medie:	n/a
Maks. flowhastighed:	n/a
Maks. driftstryk:	2500 psi, 172 bar
Pumpetype:	Fixed, Gear
Rotationsretning:	Clockwise
"Body" materiale:	Aluminum
Flowhastighed:	n/a
Fortrængning:	36.5 cm ³ /rev, 2.227 inch ³ /rev
Produkttype:	Aluminum Pump w/bearing sleeve, fixed displacement
Monteringstype:	2-Bolt SAE AA
Nominel hastighed:	500 to 4000 RPM
For væsketype:	Mineral Oil, Petroleum Based Fluids, Transmission Fluids, Phosphate-ester (w/FPM seals), Water-Glycol (w/DU Bushings), Water Emulsions (w/DU Bushings)
Maks. kontinuerligt tryk:	2500.0 psi, 172.0 bar
Vægt:	5 to 7 lb, 2.3 to 3.2 kg
Filters effektivitetsklassificering:	Maintain SAE Class 4

Akselpakningsmateriale:	NBR
Overtryksventil:	n/a
Driftstemperatur:	-40 to 185 °F, -42 to 85 °C
Maksimal kinematisk viskositet:	Startup: 4000 SUS, 1000 SUS (Operating)
Samlet længde:	4.68 inch, 118.87 mm
Rotation:	ClockWise
Porting:	UNF-2B SAE Straight Thread: 1-5/16-12 Inlet x 7/8-14 Outlet - Rear
Akseltype:	9-Tooth Spline
Pumpefortrængning (cu in/rev):	H25: .603 (9.88 cc/rev)
Overtryksventilindstilling (psig):	n/a
Flow Rate (gpm):	n/a
Valg:	n/a

