



Solenoid coil,MSN1W-230AC- OD,123062

URL:<https://www.sxplc.com/solenoid-coil-msn1w-230ac-od-123062>

Product data sheet

- | | |
|-------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|
| • Mounting position | Any |
| • Min. pick-up time | 10 ms |
| • Duty cycle | 100% |
| • Power factor cos {phi} | 0.7 |
| • Coil characteristics | 230 V AC: 50 Hz, initial power 7.5 VA, holding power 5.0 VA
230 V AC: 60 Hz, initial power 5.0 VA, holding power 3.7 VA |
| • Permissible voltage fluctuations | +/- 10 % |
| • Maritime classification | See certificate |
| • CE marking (see declaration of conformity) | As per EU low voltage directive |
| • UKCA marking (see declaration of conformity) | To UK instructions for electrical equipment |
| • Certificate issuing authority | DNV-TAA000032X |

- **LABS (PWIS) conformity**VDMA24364-C1-L
- **Temperature of medium**-10 °C ... 50 °C
- **Degree of protection**IP65
- **Ambient temperature**-10 °C ... 50 °C
- **Product weight**80 g
- **Electrical connection**3-pin Form A as per DIN EN 175301-803
- **Type of mounting**Clamped With retaining clamp With accessories
- **Housing material**PA
- **Material of pin contacts**Steel
- **Material of winding**Copper

