



**Solenoid coil,MSN1W-230AC-  
OD,123062**

URL:<https://www.sxplc.com/solenoid-coil-msn1w-230ac-od-123062>

**Product data sheet**

- |   |
|---|
| • <b>Mounting position</b> Any  |
| • <b>Min. pick-up time</b> 10 ms  |
| • <b>Duty cycle</b> 100%  |
| • <b>Power factor cos {phi}</b> 0.7   |
| • <b>Coil characteristics</b> 230 V AC: 50 Hz, initial power 7.5 VA, holding power 5.0 VA 230 V AC: 60 Hz, initial power 5.0 VA, holding power 3.7 VA |
| • <b>Permissible voltage fluctuations</b> +/- 10 %  |
| • <b>Maritime classification</b> See certificate  |
| • <b>CE marking (see declaration of conformity)</b> As per EU low voltage directive   |
| • <b>UKCA marking (see declaration of conformity)</b> To UK instructions for electrical equipment   |
| • <b>Certificate issuing authority</b> DNV-TAA000032X   |

- **LABS (PWIS) conformity**VDMA24364-C1-L
- **Temperature of medium**-10 °C ... 50 °C
- **Degree of protection**IP65
- **Ambient temperature**-10 °C ... 50 °C
- **Product weight**80 g
- **Electrical connection**3-pin Form A as per DIN EN 175301-803
- **Type of mounting**Clamped With retaining clamp With accessories
- **Housing material**PA
- **Material of pin contacts**Steel
- **Material of winding**Copper

