



LIGHT CL2-513G

URL:<https://www.sxplc.com/light-cl2-513g>

Product data sheet

Dimensions

Product Net Width:

0.03 m

Product Net Height:

0.03 m

Product Net Depth / Length:

0.052 m

Product Net Weight:

0.018 kg

Technical

Ambient Air Temperature:

Operation -25 ... +70 °C

Storage -40 ... +85 °C

Color:

Green

Actuator Type:

Pilot light head

Illumination:

Illuminated

Lamp Type:

110-13 V AC, integrated LED

Enclosure Type NEMA:

Type1

Type12

Type13

Type3R

Type4

Type4X

Pollution Degree:

3

Rated Frequency (f):

Supply Circuit 50 / 60 Hz

Rated Operational Voltage:

110 ... 130 V AC

Supply Circuit 110 ... 130 V AC

Connecting Capacity:

Flexible with Ferrule 1 x 0.75...2.5 mm²

Flexible with Ferrule 2 x 0.75...2.5 mm²

Flexible with Insulated Ferrule 1 x 0.75...2.5 mm²

Flexible with Insulated Ferrule 2 x 0.75...2.5 mm²

Flexible 1 x 0.75 ... 2.5 mm²

Flexible 2 x 0.75 ... 2.5 mm²

Solid 1 x 0.75...2.5 mm²

Solid 2 x 0.75...2.5 mm²

Connection Type:

Screw Clamp

Terminal Type:

Screw Terminals

Tightening Torque:

0.9 N·m

Wire Stripping Length:

