



Solenoid Valve JKH8321G001

URL:<https://www.sxplc.com/solenoid-valve-jkh8321g001>

Product data sheet

Valve Actuation

Solenoid - Air Pilot

Body Material

Brass, Stainless Steel

Media

Air, Inert Gas, Light Oil, Water

Pipe / Port Size

1/4 " ; 3/8 "

Port Type

NPTF

Function

3 way - 3/2 Normally Closed, 3 way - 3/2 Normally Open

Flow

From .05-.1 Cv, From 0.1 Cv to 0.5 Cv, From .43 to .86 Kv, From .86 to 1.73 Kv

Voltage

100 to 240 AC/DC Voltage Ranging, 12 to 24 DC Voltage Ranging, 125 DC Battery Charging, 110 AC, 12 DC, 120 AC, 120 DC, 24 AC, 24 DC, 24 to 120 AC/DC Voltage Ranging, 240 DC, 250 DC Battery Charging | 50, 50/60, 60

Operating Environment

Corrosive, Indoor, Outdoor

Standards / Regulations

ATEX Zone 1-21, ATEX Zone 2-22, CSA, IEC Ex Zone 1-21, SIL, Type 1, Type 2, Type 3, Type 3S, Type 4, Type 4X, Type 6, Type 6P, Type 7, Type 9, UL

Standards / Regulations

ATEX Zone 1-21, ATEX Zone 2-22, CSA, IEC Ex Zone 1-21, SIL, Type 1, Type 2, Type 3, Type 3S, Type 4, Type 4X, Type 6, Type 6P, Type 7, Type 9, UL

