



Air line lubricator LOE-D-MIDI

192576

URL:<https://www.sxplc.com/air-line-lubricator-loe-d-midi-192576>

Product data sheet

- | | |
|--|--|
| • Size | Midi |
| • Series | D |
| • Mounting position | Vertical +/- 5° |
| • Structural design | Proportional standard oil mist lubricator |
| • Max. oil capacity | 110 cm ³ |
| • Bowl guard | Metal bowl guard |
| • Symbol | 00991532 |
| • Operating pressure | 0 MPa ... 1.6 MPa |
| • Operating pressure | 0 bar ... 16 bar |
| • Operating pressure | 0 psi ... 232 psi |
| • Minimum flow rate for lubricator function | 8 l/min |
| • Operating medium | Compressed air as per ISO 8573-1:2010 [7:4:4] Inert gas |
| • Information on operating and pilot media | Operation with oil |

lubrication not possible

- **Corrosion resistance class (CRC)**2 - Moderate corrosion stress
- **LABS (PWIS) conformity**VDMA24364-B1/B2-L
- **Storage temperature**-10 °C ... 60 °C
- **Air quality class at the output**Compressed air as per ISO 8573-1:2010 [7:4:-] Inert gas
- **Temperature of medium**-10 °C ... 60 °C
- **Ambient temperature**-10 °C ... 60 °C
- **Product weight**630 g
- **Type of mounting**With accessories
- **Note on materials**RoHS-compliant
- **Material of bowl**PC

