



Ethernet switch EKI-2528-BE

URL: <https://www.sxplc.com/ethernet-switch-eki-2528-be>

Product data sheet

Ethernet Port Count

- 8

Mounting

- DIN, Panel

Power

- 12-48VDC

Technology

- Ethernet

Temperature

- -10 to 60C

Unmanaged

- Yes

Certification

EMI

- CE, FCC Class A

EMS

- EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6, EN 61000-4-8

Safety

- UL 60950-1

Environment

Temperature (Min. Operating)

- -10°C (14°F)

Temperature (Max. Operating)

- 60°C (140°F)

Operating Temperature

- -10 ~ 60°C (14 ~ 140°F)

Storage Temperature

- -40 ~ 85°C (-40 ~ 185°F)

Ethernet Communication

Fiber Port Number

- -

Fiber Port Interface

- -

Fiber Port Connector Type

- -

Fiber Transmission Distance

- -

Fiber Transmission Speed

- -

RJ-45 Port Number

- 8

RJ-45 Port Connector Type

- RJ-45

RJ-45 Transmission Distance

- 100 m

RJ-45 Transmission Speed

- 10/100 Mbps

Mechanism

Mounting (DIN-rail)

- Yes

Mounting (Stack)

- -

Mounting (Panel)

- -

Mounting (Wall)

- Yes

Mounting (Rack Mount)

- -

Mounting (Pole Mount)

- -

Dimensions (W x H x D)

- 30 x 140 x 95 mm (1.18' x 5.51' x 3.74 in.)

Enclosure (Plastic)

- -

IP Rating

- IP30

PoE Information

PoE Port Number

- -

PoE Budget

- -

PoE Output

- -

Support PoE

- No

Power

Power Connector Type

- 6-pin removable screw terminal

Power Consumption

- 4.71W

Power Input (AC)

- -

Power Input (DC)

- 12 ~ 48 VDC

Power Input (PoE)

- -

Power Input (Battery)

- -

Redundant Dual Inputs

- Yes

Warranty

Warranty Period

- 5 years

Protection

Overload Current

- Present

Reverse Polarity

- Present

